

## New ProSub 800 and ProSub 1000 Subwoofers

The ProSubs are also completely new and incorporate SuperCube technology for dramatically improved bass performance. Specially engineered 8" or 10" high velocity long-throw drivers are combined with downward firing pressure-coupled mediate sub-bass radiators and 300 watt digital amplifiers for exceptional low frequency response. The ProSubs are capable of reproducing the subtlest nuances of the finest musical performance as well as the dramatic floor shaking impact of the most demanding cinematic action extravaganzas. The high density mediate cabinets are attractively finished in matte black and incorporate a convenient side-mounted volume control.

### SPECIFICATIONS:

**ProSub 800:** Dimensions: 12<sup>7</sup>/<sub>8</sub>"H x 15<sup>3</sup>/<sub>4</sub>"D x 10<sup>5</sup>/<sub>16</sub>"W. Driver Complement: One 8" woofer with polymer cone coupled to one 8" infrasonic radiator. Amplifier: 300 Watts RMS. Speaker Level High-Pass Filter: 6 db/octave (80 Hz). High-Level Low-Pass Filter: 24 db/octave continuously variable (40 Hz – 150 Hz) plus unfiltered LFE direct-coupled input. Frequency Response: 20 Hz – 150 Hz.

**ProSub 1000:** Dimensions: 14<sup>7</sup>/<sub>16</sub>"H x 17<sup>7</sup>/<sub>8</sub>"D x 12"W. Driver Complement: One 10" woofer with polymer cone coupled to one 10" infrasonic radiator. Amplifier: 300 Watts RMS. Speaker Level High-Pass Filter: 6 db/octave (80 Hz). High-Level Low-Pass Filter: 24 db/octave continuously variable (40 Hz – 150 Hz) plus unfiltered LFE direct-coupled input. Frequency Response: 18 Hz – 150 Hz.



ProSub 1000 & 800

*Definitive Technology®*  
The Leader in High-Performance Loudspeakers®